

STOPGAP PI21



Acrylic Primer

An acrylic primer designed to promote the adhesion of Stopgap levelling compounds over synthetic anhydrite screeds.

GENERAL USE

Calcium sulphate screeds (e.g anhydrite).

CHARACTERISTICS

- ✓ Pigmented to provide coverage control
- ✓ Prevents the rapid drying of adhesives and levelling compounds

COVERAGE

10m² per litre
First coat diluted 1 part primer with 1 part water
Second coat neat

STOPGAP PI31



General Purpose Primer

Neoprene emulsion primer designed to prevent rapid drying of adhesives and levelling compounds.

GENERAL USE

To promote adhesion of Stopgap levelling compounds to both absorbent and non-absorbent surfaces.

CHARACTERISTICS

- ✓ Suitable for use with F. Ball marine applications
- ✓ Pigmented to provide coverage control
- ✓ Prevents the rapid drying of adhesives and levelling compounds

COVERAGE

20m² – 35m² per litre
When diluted with water*
10m² per litre
Neat
*Refer to technical data sheet

STOPGAP PI41



Primer For Non-Absorbent Surfaces

An acrylic primer designed to provide a textured surface, to provide increased adhesion to floor levelling compounds.

GENERAL USE

To promote adhesion of Stopgap levelling compounds to non-absorbent surfaces.

CHARACTERISTICS

- ✓ Textured surface for increase adhesion
- ✓ Fast Drying
- ✓ Increased Coverage
- ✓ Pigmented to provide coverage control

COVERAGE

Up to 13m² per litre
Neat

STOPGAP FILL & PRIME



Flexible Cement Based Primer *Two Component*

Designed to have a thixotropic consistency which enables joints up to 4mm to be filled in raised access panels. Applied up to a thickness of 1mm, it sets rapidly and is ready to receive foot traffic in as little as 60 minutes. Once cured, the flexible nature of the product will accommodate movement within the substrate.

GENERAL USE

Suitable for use over raised access panels and substrates with well bonded, waterproof residues of adhesives prior to the direct application of Stopgap 1200 PRO. It can be applied to flooring grade wooden substrates such as plywood, orientated strand board (OSB 3), particle board (chipboard) conforming to BSEN 312 Annex A P4-P7 and medium density fibreboard, prior to the application of Stopgap 700 Superflex. It may also be used to smooth out uneven tongue and groove floorboards prior to over boarding with plywood.

CHARACTERISTICS

- ✓ Fast drying
- ✓ Excellent flexibility
- ✓ Thixotropic to allow filling of joints up to 4mm wide

COVERAGE

8.5m² at 0.5mm thickness

STYCCOCLEAN CI40



Floor Cleaner

Concentrated alkaline liquid detergent for the removal of grease, oil and some adhesive. Can also be used to strip emulsion based polish from floorcoverings.

GENERAL USE

Asphalt, tarmac, concrete, sand/cement screed, granolithic, ceramic, quarry tiles and terrazzo.

CHARACTERISTICS

- ✓ Cleans a wide range of contaminants
- ✓ Suitable for use on a wide variety of floorcoverings

STYCCOCLEAN SOLVENT



Contaminant Remover

A non-flammable solvent.

GENERAL USE

Used for the removal of contaminants such as grease and oil from the back of floorcoverings and accessories prior to installation. Also assists in the removal of some adhesives from the surface of carpets and floorcoverings.

CHARACTERISTICS

- ✓ Fast drying
- ✓ Non-flammable
- ✓ Removes grease, oil and some adhesives
- ✓ Easy to apply