

Vebe Floorcoverings by Inslag 12, 8281 JV P.O. Box 11, 8280 AA

(+31) 38 385 32 00 F (+31) 38 385 61 87 Е info@vebe.net Genemuiden, The Netherlands W www.vebe.net

Metropolis 1000 Dilo	oui OX			
Manufacturing process	Needlefelt			ISO 2424
Surface aspect	Dilour			ISO 2424
Dimensions	200 cm			
Backing	OL			ISO 2424
Pile yarn composition	100% PP			
Pile weight	950 g/m²			
Total weight	1900 g/m²		+/- 10%	ISO 8543
Pile height	4 mm	4 mm		ISO 1765
Total height	10 mm +/- 10%			ISO 1765
Overall use class	Domestic	Domestic 23, Areas with heavy use		
uxury class	LC2	LC2		EN 1307
Colour fastness to light	≥ 5			ISO 105-B02
Colour fastness to rubbing, wet and dry	≥ 4			ISO 105-X12
Colour fastness to water	≥ 4		ISO 105-E01	
Colour fastness to soiling	≥ 3		EN 1269	
Dimensional stability	Shrinkage ≤ 1,2 %			ISO 2551
	Extension ≤ 0,5 %		ISO 2551	
Electrostatic charging	< 2kV			ISO 6356
Slip resistance	> 0,3	Machine direction		EN 13893
	> 0,3	Crossdirection		EN 13893
Flammability	Efl			EN 13501-1

Floorsymbols















Certificates



Vebe Floorcoverings b.v. certifies the supplied products to meet the requirements as specified and stated in the last editions of the technical information. The products have been produced and tested according procedures agreed in our quality system (according ISO 9001). The tests have been carried out according to the prescribed standards.

