

iQ Eminent

TECHNICAL DATA

CERTIFICATION & CLASSIFICATION	STANDARDS	iQ Eminent
Type of floor covering	ISO 10581	Pressed homogeneous single layered vinyl flooring
Declaration of performance	EN 14041	0019-0008-DoP-2013-07
Binder content	ISO 10581	Type I
Classification	ISO 10874	Commercial: 34 Industrial: 43
Recyclable	ISO 14021	Yes, post installation and post use

TECHNICAL CHARACTERISTICS		
Surface treatment		iQ
Surface restoration		Yes
Total thickness	ISO 24346	2.0 mm
Wear layer thickness	ISO 24340	2.0 mm
Total weight	ISO 23997	2750 g/m ²
Form of delivery iQ Eminent	ISO 24341 Sheet (rolls)	Approx. 23 running metres x 200 cm Art. no. 21030_ _ _ 3 digit colour number
	ISO 24342 Tiles (box)	61.0 x 61.0 cm – 14 tiles/box = 5.21 m ² Art. no. 21031_ _ _ 3 digit colour number
Form of delivery iQ Eminent bio-attributed	ISO 24341 Sheet (rolls)	Approx. 23 running metres x 200 cm Art. no. 21146_ _ _ 3 digit colour number
	ISO 24342 Tiles (box)	61.0 x 61.0 cm – 14 tiles/box = 5.21 m ² Art. no. 21147_ _ _ 3 digit colour number

TECHNICAL PERFORMANCES		
Reaction to fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class B _{fl} s1 ≥ 8 kW/m ² Pass
Residual indentation	ISO 24343-1	Required value: ≤ 0.10 mm Best measured value: 0.02 mm
Castor chair test	ISO 4918	Suitable
Static electrical discharge	EN 1815 On any surface ≤ 10 ⁹ Ω	< 2 kV
Clean room	ISO 14644-1	ISO class 4
Riboflavin test	Fraunhofer method	Class 0: Excellent
Total VOC emissions	ISO 16000-6 Indoor air quality FloorScore	≤ 10 µg/m ³ (after 28 days) Platinum SCS certified
Underfloor heating		Suitable – max 27°C
Light fastness	EN ISO 105-B02	≥ level 7
Ease of decontamination	ISO 8690 – DIN 25415	Excellent
Chemical resistance	ISO 26987	Excellent
Bacteria resistance	ISO 846:Part C	Does not favour growth
Slip resistance	DIN 51130 EN 13893 BS 7976-2	R9 ≥ 0.3 Low risk of slip
Wet room approval	EN 13553 Annex A	Watertight

COLOURS

26

The above information is subject to modification for the benefit of further improvement (04/2021).

According to the European Regulation N° 305/2011 for CE Marking, the Declarations of Performance are available on our website www.tarkett.com

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.

