

iD SQUARE

TECHNICAL DATA

Classification	Standards	iD Square	
Classification	EN ISO 10582 / EN 651	Heterogeneous Acoustic Resilient Floorcovering	
	EN ISO 10874	Commercial: 34	
Wear layer binder content	EN ISO 10582	Type I	
Technical characteristics			
Total thickness	EN ISO 24346	4,5 mm	
Wear layer thickness	EN ISO 24340	0,80 mm	
Total weight	EN ISO 23997	5195 g/m ²	
Bevelled edges	-	No	
Surface treatment (PUR)	-	Yes - TopCleanXP™	
Form of delivery	EN ISO 24342		
	Planks	25 x 100 cm 20 x 120 cm 20 x 120 cm Left chevron 20 x 120 cm Right chevron	9 planks/box = 2.25 m ² 10 planks/box = 2,40m ² 10 planks/box = 2,40m ² 10 planks/box = 2,40m ²
	Tiles	50 x 50 cm 66 x 66 cm 100 x100 cm	9 tiles/box = 2.25 m ² 5 tiles/box = 2.22 m ²
Performance for CE marking requirement (EN 14041)			
Declaration Of Performance	EN 14041	0120-0067-DoP-2014-11	
Reaction to fire	EN 13501-1	B _{fl} s1 loose-laid on an A1 _{fl} and/or A2 _{fl} substrate C _{fl} s1 loose-laid on a wooden sub-floor	
Electrostatic properties	EN 1815 EN 1081	<2 kV on concrete > 10 ⁹ Ohm	
Thermal resistance	EN ISO 10456	0,05 m ² K/W	
Antislip classification	EN 13893	μ ≥ 0.30	
Technical performances			
Dimensional stability	EN ISO 23999	≤ 0,10 %	
Impact sound reduction	EN ISO 717-2	ΔL _w = 15 dB	
Reduction of in-room impact noise	EN ISO 31-074	Class B - L _{n,e,w} = < 75 dB	
Accoustical absorption	EN ISO 11654	∞ W = 0.05	
Slip resistance	DIN 51130	R10/R11 depending on Embossing	
Furniture leg	EN 424	No damage	
Castor chair	ISO 4918	No damage	
Light fastness	EN ISO 105-B02	≥ 6	
Residual indentation	EN ISO 24343-1	≤ 0,10 mm	
Chemical resistance	EN ISO 26987	Very good	
Underfloor heating	-	Suitable - max. 27 °C	
Environmental performances			
Total VOC emission	ISO 16000-9	<10 µg/m ³ (after 28 days)	
Recyclable	-	100%	
Plasticizer	-	Phthalate-free	

The above information is subject to modification for the benefit of further improvement. (12/18).
Tarkett's instructions regarding installation, cleaning and maintenance should be observed.
Please contact Tarkett at the address shown for these instructions.

CUSTOMS TARIFF : 4820 5000 00

