




HOMOGENEOUS VINYL  
SAFETY FLOORCOVERING

## Granit Safe.T



- > Excellent slip resistance properties
- > 2 mm wear layer for extreme durability
- > Approved also for wetrooms



When safety  
is a priority



A crucial part of flooring comfort is safety under foot. In some areas there is an increased risk for slip and fall injuries, and the right flooring can prevent most of them. The unique safety features of Granit Safe.T provide a slip resistance rating of R10. It is recommended for use in healthcare premises, schools, leisure areas, shops and similar commercial areas, whenever safety properties are required.

### **Solid, homogeneous construction**

Granit Safe.T is a homogeneous floorcovering with anti slip properties. The homogeneous construction ensures extreme toughness and durability, and gives the flooring a superior life cycle cost. It also makes Granit Safe.T ideal for wet areas, and it is wet room approved.

### Part of extended Granit family

The Granit family from Tarkett includes the very popular iQ Granit, and floorcoverings for acoustic needs, for ESD-control, for wetrooms and Granit Safe.T for anti slip properties in all types of areas including wetrooms. All Granit ranges are colour coordinated, to allow a unified flooring appearance for all different types of areas in a building.




## The Granit Safe.T colour range



2 mm: 690



2 mm: 691



2 mm: 692



2 mm: 696



2 mm: 695



2 mm: 694



2 mm: 693




2 mm: 697



2 mm: 698



2 mm: 699



2 mm: 700

### Safety Clean for easy maintenance

Tarkett's unique Safety Clean surface treatment makes Granit Safe.T very hardwearing and much easier to clean and maintain than traditional safety floorings.

### Trouble-free installation

The raw material composition in a homogeneous construction also gives the floorcovering great installation properties. It is very flexible and easy to work with, and coving up a wall or vertical surface is no problem. The less abrasive construction is also kinder for installers to work with and causes less damage and blunting to installation tools.

## Tarkett's Balanced Choice

Granit Safe.T is part of Tarkett's choice of sustainable solutions, an integrated system that allows for balancing all the competing needs, while making choices that are truly sustainable and work together aesthetically.



### BETTER MATERIALS

*Where we can use renewable resources, we do*



### RESOURCE STEWARDSHIP

*Using fewer resources is good for the environment and the bottom line*



### PEOPLE-FRIENDLY SPACES

*We make floors that help people work, play, shop, heal and learn better*



### REUSE AND RECYCLE

*We find ways to use more recycled content at the start and recycle more product at the end*

# Granit Safe.T

## Specification

Granit Safe.T is a homogeneous vinyl safety flooring suitable for use in commercial and wet room areas. Available in sheet form, 11 colourways, colour- and pattern-coordinated with the extended iQ Granit family. Granit Safe.T is equipped with Safety clean surface for easier cleaning and better hygiene. Available with plain and multicolour welding rods.

CERTIFICATION & CLASSIFICATION	STANDARDS	Granit Safe.T
Type of flooring	EN 13485	Slip resistant homogeneous vinyl flooring
CE certification		Yes
Classification	EN 685	Commercial: 34 Industrial: 43
TECHNICAL CHARACTERISTICS	STANDARDS	Granit Safe.T
Wear layer thickness	EN 429	2.0 mm
Surface treatment		Safety clean
Total thickness	EN 428	2.0 mm
Total weight/m <sup>2</sup>	EN 430	3000 g
Form of delivery	EN 426	Approx. 25 m x 200 cm
	Sheet (rolls)	art. no. 3052_ _ _ 3 digit colour number
TECHNICAL PERFORMANCES	STANDARDS	Granit Safe.T
Dimensional stability	EN 434	≤ 0.40 %
<b>Abrasion</b>		
Thickness loss	EN 660: Part 1	Group P: ≤ 0.15 mm
Volume loss	EN 660: Part 2	Group P: ≤ 4.00 mm <sup>3</sup>
Residual indentation	EN 433	Approx. 0.03 mm
Castor chair test	EN 425	Suitable
Static electrical charge	EN 1815	< 2 kV
Underfloor heating		Suitable – max. 27° C
Impact sound resistance	EN ISO 717/2	Approx. + 4 dB
Thermal resistance	EN 12667/DIN 52612	Approx. 0.01 m <sup>2</sup> K/W
Reaction to fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class B <sub>s1</sub> ≥ 8 kW/m <sup>2</sup> Pass
Light fastness	EN ISO 105-B02	≥ Level 6
Chemical resistance	EN 423	Good resistance
Fungi and Bacteria resistance	DIN EN 846-A/C	Does not favour growth
Slip resistance	DIN 51130 EN 13893	R10 ≥ 0.3
Bare foot test	DIN 51097	Class B (≥ 18°)
Colours		11

The information is subject to modification for the benefit of further improvement (06/09). For more detailed technical information, please contact Tarkett. Please follow Tarkett's installation and maintenance instructions, included on the packaging, carefully.



Granit Safe.T	WELDING RODS NO		NCS-CODES
	PLAIN	MULTICOLOUR	
690	1287 249	1290 056	S 1040-Y30R
691	1288 255	1290 036	S 1005-Y40R
692	1287 407	1290 023	S 2010-Y30R
693	1292 375	1290 046	S 3030-Y50R
694	1287 332	1290 059	S 3020-G30Y
695	1291 210	1290 038	S 2020-R90B
696	1292 379	1290 041	S 4030-R90B
697	1291 811	1290 028	S 2502-B
698	1292 383	1290 021	S 4502-B
699	1288 327	1290 027	S 6502-B
700	1292 384	1290 035	S 8502-B

■ **Australia:** Tarkett Australia Pty Ltd - Tel. +61 2 96 34 73 73 ■ **Austria:** Tarkett Holding GmbH, Niederlassung Wien - Tel. +43 1 478 80 62 ■ **Baltic States:** Tarkett Wykladziny Sp. z o.o. - Tel. +370 37 262 220 ■ **Belgium:** S.A. Tarkett NV - Tel. +32 16 35 98 80 ■ **Brazil:** Tarkett FADEMAC - Tel. +55 12 3954 7244 ■ **Canada:** Tarkett Inc. - Tel. +1 450 293 173 ■ **China:** Tarkett Asia Pacific Limited - Shanghai Representative Office - Tel. +86 21 6095 6838 / +86 21 6095 6859 ■ **Czech Republic:** Tarkett SAS, org. slozka - Tel. +420 271 001 602 ■ **Denmark:** Tarkett A/S - Tel. +45 43 90 60 11 ■ **Finland:** Tarkett Oy - Tel. +358 9 5406 5870 ■ **France:** Tarkett France - Tel. +33 1 41 20 42 49 ■ **Germany:** Tarkett Holding GmbH, Bereich Objekt - Tel. +49 (0) 62 33 810 ■ **Greece:** Tarkett Monoprosopi Ltd - Tel. +30 2 10 576 3889 ■ **Hong Kong:** Tarkett Asia Pacific Ltd. - Tel. +852 251 18 716 ■ **Hungary:** Tarkett SAS - Tel. +36 1 437 8150 ■ **Italy:** Tarkett S.p.A. - Tel. +39 02 893 411 ■ **Luxembourg:** Tel. +352 949 211 8804 ■ **Middle East:** Tarkett Middle East - Tel. +961 151 3363/4 ■ **Netherlands:** Tarkett Holding GmbH - Vestiging Nederland - Tel. +31 76 57 80 760 ■ **Norway:** Tarkett AS - Tel. +47 32 20 92 00 ■ **Poland:** Tarkett Wykladziny Sp. z o.o. - Tel. +48 22 639 31 66 ■ **Portugal:** Tarkett SA - Tel. +351 21 427 64 20 ■ **Russian Federation:** Tarkett Russia - Tel. +7 4 95 777 69 83 ■ **Slovakia:** Tarkett SAS - Tel. +421 248 291 317 ■ **Singapore:** Tarkett Far East - Tel. +65 67 43 53 84 ■ **South East Europe:** Tarkett Trade d.o.o. - Tel. +381 21 7557 649 ■ **Spain:** Tarkett Floors S.L. - Tel. +34 91 358 00 35 ■ **Sweden:** Tarkett Sverige AB - Tel. +46 771 25 19 00 ■ **Switzerland:** Tarkett Holding GmbH, Bereich Objekt Schweiz - Tel. +41 (0) 43 233 79 24 ■ **Turkey:** Tarkett ASPEN - Tel. +90 212 213 65 80 ■ **Ukraine:** Tarkett UA - Tel. +380 (44) 569 12 21 ■ **United Kingdom:** Tarkett Ltd - Tel. +44 (0) 1622 854 040 ■ **North America:** Johnsonite - Tel. +1 440 543 8916 ■ **Tarkett Inc. USA** - Tel. +1 713 869 5811 ■ **Latin America:** Tarkett FADEMAC - Tel. +55 12 3954 7244 ■ **Tarkett International:** Tel. +33 1 41 20 41 01