

ART FUSION

FUSION COLLECTION

**HIGH
PERFORMANCE
COLLECTIONS**

CONSTRUCTION STRUCTURE STRUKTUR STRUCTUUR	ituft 1/12" loop ituft 1/12" bouclé ituft 1/12" Schlinge ituft 1/12" lussenpool	CASTOR CHAIR SUITABILITY CHAISE À ROULETTES STUHLROLLENEIGNUNG ROLSTOELGESCHIKTHEID	EN 985 A: intensive use
PILE MATERIAL COMPOSITION DU VELOURS POLMATERIAL POOLMATERIAAL	100% PA 6 solution dyed	STAIR SUITABILITY ESCALIERS TREPPENEIGNUNG TRAPPENGESCHIKTHEID	EN 1963 A: intensive use
PRIMARY BACKING SUPPORT TRÄGERMATERIAL TUFTDOEK	Non woven PES Non tissé PES Vlies, PES Vilt, PES	PERMANENTLY ANTISTATIC ANTISTATIQUE PERMANENT PERMANENT ANTISTATISCH PERMANENT ANTISTATISCH	ISO 6356 < 2 kV
SECONDARY BACKING DOSSIER RÜCKEN TAPIJTRUG	Twin back	IMPACT NOISE RATING ISOLATION PHONIQUE TRITTSCHALLVERBESSERUNG GELUIDSISOLATIE	ISO 140-8 26 dB ΔLw
PILE WEIGHT POIDS DU VELOURS POLEINSATZGEWICHT POOLGEWICHT	± 780 gr/m ²	SOUND ABSORPTION ABSORPTION PHONIQUE SCHALLABSORPTIONSGRAD GELUIDSABSORPTIE	ISO 354 0,25 αw
TOTAL WEIGHT POIDS TOTAL GESAMTGEWICHT TOTAAL GEWICHT	± 2.200 gr/m ²	THERMAL RESISTANCE RÉSISTANCE THERMIQUE WÄRMEDURCHLASSWIDERSTAND WARMTEDOORLAATWEERSTAND	ISO 8302 0,10 m ² K/W
PILE HEIGHT EPAISSEUR DU VELOURS POLHÖHE POOLHOOGTE	± 4,2 mm	FASTNESS TO LIGHT SOLIDITÉ À LA LUMIÈRE LICHTECHTHEIT LICHTECHTHEID	ISO 105-B02 ≥ 7
TOTAL HEIGHT EPAISSEUR TOTALE GESAMTHÖHE TOTALE HOOGTE	± 7,8 mm	COLOUR FASTNESS TO WATER SOLIDITÉ À L'EAU WASSERECHTHEIT WATERECHTHEID	EN ISO 105-E01 ≥ 4-5
TUFT DENSITY NOMBRE DE POINTS NOPPENZAHL AANTAL PUNTEN	± 282.000/m ²	RUBBING FASTNESS SOLIDITÉ AU FROTTEMENT REIBECHTHEIT WRIJFECHTHEID	EN ISO 105-X12 ≥ 4
PILE DENSITY DENSITÉ DU VELOURS POLROHDICHTHEIT POOLDICHTHEID	± 0,129 g/cm ³	FIRE RESISTANCE COMPOTEMENT AU FEU BRENNVERHALTEN BRANDGEDRAG	EN 13501-1 Cfl-s1
CLASSIFICATION CLASSEMENT KLASSIFIKATION CLASSIFICATIE	EN 1307 32 - LC2	WIDTH LARGEUR BREITE BREEDTE	EN ISO 3018 ± 400 cm
DESIGN REPEAT (CM) RACCORD (CM) RAPPORT (CM) DESSINRAPPORT (CM)	± 199 (W) x ± 306 (H) repeatless installation possible		
PRODIS / GUT	F42F52E2		



ITC CO BV
Kanegemstraat 15, B-8700 Tielt
itc-carpets.com



EN 14041 CE
21
ITC CO BV Kanegemstraat 15 - BE 8700 Tielt
DOP: 1011#IEOACL
Textile Floor Covering EN1307 Notified Body 2401
my.itc-carpets.com