

Dynamic

Tuft gauge	1/10 loop pile		ISO 2424
Pilecomposition	100% PA SDN		ISO 2424
Primary Backing	Woven		ISO 2424
Secondary backing	AB		ISO 2424
Width	400 cm, 500 cm	± 1%	EN 984
Pile Weight	720 gr/m ²		ISO 8543
Total weight	AB : 1550 gr/m ²	± 15%	ISO 8543
Pile height	3 mm	± 2 mm	ISO 1766
Total Height	AB : 5 mm		ISO 1765
Number of knots	197.500/m ²	-7.5% .+10%	ISO 1763
Fire Classification	Cfl-S1	EN 13501-1	
Use Area	Heavy project use (33)		EN 1307
GUT Nr.	FDAAA0DC GUT		www.pro-dis.info
Thermal resistance	0.076 M ² KW		ISO 8302
Light fastness	≥ 5		105-B02
Wearebility	≥ 4		105-X12
Water fastness	≥ 4		105-E01
Electrostatic charging	<2 kV		ISO 6356
Luxury class	LC1		EN 1307
Pictures	www.condorcontract.com		

Floorsymbols



Certificates

CE
2019
Condor Carpets
Euroweg 3
8061 SB Hasselt
EN1307
DOP: C-022AD171
Reaction to fire:
Cfl-s1
1668
Slip resistance: DS
Resilient floor
covering to be
used within a
building





