

CONSTRUCTION	Tufting 5/64" twist pile
STRUCTURE	Tufté 5/64" frisé
STRUKTUR	Getuftet 5/64" frisé
STRUCTUUR	Getuft 5/64" frizée
PILE MATERIAL	100% PA 6 IMPREL®
COMPOSITION DU VELOURS	
POLMATERIAL	
POOLMATERIAAL	
PRIMARY BACKING	woven PP
SUPPORT	PP tissé
TRÄGERMATERIAL	PP Bändchen
TUFTDOEK	geweven PP
SECONDARY BACKING	Action Back
DOSSIER	
RÜCKEN	
TAPIJTRUG	
PILE WEIGHT	Ca. 1.200 gr/m ²
POIDS DU VELOURS	
POLEINSATZGEWICHT	
POOLGEWICHT	
TOTAL WEIGHT	Ca. 2.027 gr/m ²
POIDS TOTAL	
GESAMTGEWICHT	
TOTAAL GEWICHT	
PILE HEIGHT	Ca. 5,6 mm
EPAISSEUR DU VELOURS	
POLHÖHE	
POOLHOOGTE	
TOTAL HEIGHT	Ca. 7,7 mm
EPAISSEUR TOTAL	
GESAMTHÖHE	
TOTALE DIKTE	
TUFT DENSITY	Ca. 278 400/m ²
NOMBRES DE POINTS	
NOPPENZAHL	
AANTAL PUNTEN	
PILE DENSITY	Ca. 0.168 g/cm ³
DENSITÉ DU VELOURS	
POLROHDICHTÉ	
POOLDICHTHEID	

CLASSIFICATION	EN 1307
CLASSEMENT	32 - LC4
KLASSIFIKATION	
CLASSIFICATIE	

CASTOR CHAIR SUITABILITY	EN 985
CHAISE À ROULETTES	A: intensive use
STUHLROLLENEIGNUNG	
ROLSTOELGESCHIKTHEID	

STAIR SUITABILITY	EN 1963
ESCALIERS	A: intensive use
TREPPENEIGNUNG	
TRAPPENGESCHIKTHEID	

PERMANENTLY ANTISTATIC	ISO 6356
ANTISTATIQUE PERMANENT	< 2 kV
PERMANENT ANTISTATISCH	
PERMANENT ANTISTATISCH	

IMPACT NOISE RATING	ISO 140-8
ISOLATION PHONIQUE	26 dB ΔLw
TRITTSCHALLVERBESSERUNG	
GELUIDSISOLATIE	

SOUND ABSORPTION	ISO 354
ABSORPTION PHONIQUE	0.15 αw
SCHALLABSORPTIONSGRAD	

THERMAL RESISTANCE	ISO 8302
RÉSISTANCE THERMIQUE	0,08 m ² K/W
WÄRMEDURCHLASSWIDERSTAND	
WARMTEDOORLAATWEERSTAND	

FASTNESS TO LIGHT	ISO 105-B02
SOLIDITÉ A LA LUMIÈRE	≥ 5-6
LICHTECHTHEIT	
LICHTECHTHEID	


COLOUR FASTNESS TO WATER	EN ISO 105-E01
SOLIDITÉ À L'EAU	≥ 4-5
WASSERRECHTHEIT	
WATERECHTHEID	

FIRE RESISTANCE	EN 13501-1
COMPORTEMENT AU FEU	Cfl-s1
BRENNVERHALTEN	if glued
BRANDGEDRAG	

RUBBING FASTNESS	EN ISO 105-X12
SOLIDITÉ AU FROTTEMENT	≥ 4
REIBECHTHEIT	
WRIJFECHTHEID	


NUMBER OF COLOURS	18
NOMBRES DE COULEURS	
ANZAHL FARBEN	
AANTAL KLEUREN	

WIDTH	EN ISO 3018
LARGEUR	ca. 400 + 500 cm
BREITE	
BREEDTE	



EN14041
CE
15
Balta Industries - Kanegem- straat 15 - BE 8700 Tielt
DOP: 1011#IE0ACV
Textile Floor Covering EN1307
Notified body 2401
www.baltamediabank.com


evolve A B



▲ 23



▲ 93



▲ 92



▲ 15




▲ 39



▲ 33



▲ 38



▲ 95



▲ 65



▲ 43




▲ 49




▲ 94



▲ 98



▲ 72



▲ 77



▲ 79



▲ 97



▲ 99