

ROXANE

SHOW COLLECTION

CONSTRUCTION STRUCTURE STRUKTUR STRUCTUUR	Tufting 1/10" cut pile Tufté 1/10" cut pile Getuftet 1/10" cut pile Getuft 1/10" cut pile	FASTNESS TO LIGHT SOLIDITÉ A LA LUMIÈRE LICHTECHTHEIT LICHTECHTHEID	EN ISO 105-B02 ≥ 5-6
PILE MATERIAL COMPOSITION DU VELOURS POLMATERIAL POOLMATERIAAL	100% PA	COLOUR FASTNESS TO WATER SOLIDITÉ À L'EAU WASSERECHTHEIT WATERECHTHEID	EN ISO 105-E01 ≥ 4-5
SECONDARY BACKING DOSSIER RÜCKEN TAPIJTRUG	Ultratex® back	FIRE RESISTANCE COMPORTEMENT AU FEU BRENNVERHALTEN BRANDGEDRAG	EN 13501-1 C _{FL-s} 1 if glued
PILE WEIGHT POIDS DU VELOURS POLEINSATZGEWICHT POOLGEWICHT	± 450 gr/m²	WIDTH LARGEUR BREITE BREEDE	EN ISO 3018 ca. 400 cm
TOTAL WEIGHT POIDS TOTAL GESAMTGEWICHT TOTAAL GEWICHT	± 1.290 gr/m²	UPEC CERTIFICATION	U2sP2E1C0 n° 07/231
PILE THICKNESS ÉPAISSEUR DU VELOURS POLDICKE POOLDIKTE	± 4 mm		
TOTAL THICKNESS ÉPAISSEUR TOTALE GESAMTDICKE TOTALE DIKTE	± 8 mm		
TUFT DENSITY NOMBRE DE POINTS NOPPENZAHL AANTAL PUNTEN	± 236.400/m²		
PRODIS / GUT	4DEC5FAE		
CLASSIFICATION CLASSEMENT KLASSIFIKATION CLASSIFICATIE	EN 1307 22 - LC1		G NCS 0,30 28



BALTA INDUSTRIES
Wakkensteenweg 2, B-8710 Sint-Baafs-Vijve
balta-carpet.com

EN 14041 CE
17
BALTA INDUSTRIES Kanegenstraat 15 - BE 8700 Tielt
DOP: 1011#IE00CV
Textile Floor Covering EN1307 Notified Body 2401
   
www.baltamediabank.com