CONDOR GRASS

Condor Grass Randweg 14, 8061 RW P.O. Box 21, 8060 AA Hasselt, The Netherlands (+31) 38 477 89 11 (+31) 38 477 89 22 info@condorgrass.com

W www.condor-group.eu

Т

F

Е

Allround

Amound			
Туре	Tufted synthetic grass carpet		
Material	PE Monofilament straight & PP Monofilament curled (UV Stabilized)		
Yarn type	12.000 / 6 dTex PE monofilament straight $\&$ 4.000 / 8 dTex PP monofilament curled		
Yarn quality	Environmental friendly, free of lead and cadmium		
Primary backing	100% PP black double without fleece, Weight 213 gr/m2		
Secondary backing	Black Latex compound with a base of styrenebutadiene (SBR), with drainage holes, Weigh		
	836 gr/m2		
Waterpermeability	60 liter/min/m2		
Pile height	30 mm		
Face weight	1.720 gr/m2	± 10%	
Total weight	2.769 gr/m2	± 10%	
Tuft gauge	3/8 gauge		
Stitches per 10 cm linear	14	± 1	
Stitches per m2	14.700	± 10%	
Colour	Mix of light and dark green + brown		
UV stability	Meets DIN 53387 Standard (6000 hours)		
Colour fastness	Xenon Test: Blue Scale > 7, Grey-scale > 4		
Colour lining	Not Applicable		
Roll width	200 cm, 400 cm		
Roll length	20-25m		
Applications	Gardens, Landscaping		
Infill advice	Silica sand, gradation 0,5 - 1,0 mm, 80% roundshaped, appr. 8 - 10 kg/m2		
Comments	Before installation make sure the rol	Before installation make sure the rolls are from the same production code (first five digits of	
	the roll number) Project.		



Condor Grass has the right to alter each product specification in order to improve the carpet according to the newest technological applications. Condor Grass is not legally liable in case of non-compliance with the above-mentioned specifications. The above mentioned specifications are for reference, and can only be used informal.

