

Condor Grass Euroweg 3, 8061 SB P.O. Box 21, 8060 AA Hasselt, The Netherlands T (+31) 38 477 89 11 F (+31) 38 477 89 22 E info@condorgrass.com W www.condor-group.eu

Туре	Tufted synthetic grass carpet	
Material	PE Monofilament straight & PP Monofilament curled (UV Stabilized)	
Yarn type	4.000 / 8 dTex PE monofilament straight $\&$ 3.200 / 8 dTex PP monofilament curled	
Yarn quality	Environmental friendly, free of lead and cadmium	
Primary backing	100% PP black with fleece, UV Stabilized, Weight 100 gr/m²	
Secondary backing	Black Latex compound with a base of styrenebutadiene (SBR), with drainage holes, Weight	
	684 gr/m²	
Waterpermeability	60 liter/min/m²	
Pile height	30 mm	
Face weight	1.335 gr/m²	± 10%
Total weight	2.119 gr/m²	± 10%
Tuft gauge	5/16 gauge	
Stitches per 10 cm linear	20	± 1%
Stitches per m <sup>2</sup>	25.200	± 10%
Colour	Mix of light and dark green + Field-Jute thatch	
UV stability	Meets DIN 53387 Standard (6000 hours)	
Colour fastness	Xenon Test: Blue Scale > 7, Grey-scale > 4	
Colour lining	Not Applicable	
Roll width	200 cm, 400 cm	
Roll length	20-25m	
Applications	Gardens, Landscaping, Terraces	
Infill advice	Silica sand, gradation 0,5 - 1,0 mm, 80% roundshaped, appr. 6 - 8 kg/m2	
Comments	Before installation make sure the rolls are from the same production code (first five digits of the roll number) Project.	







Condor Grass has the right to alter each product specification in order to improve the carpet according to the newest technological applications. Condor Grass is not legally liable in case of non-compliance with the above mentioned specifications. The above mentioned specifications are for reference, and can only be used informal.

The appearance of the final artificial grass carpet may change when it reaches temperatures beyond 75°C.

