


Schools DT

Type	Tufted filled synthetic grass carpet	
Material	PE Monofilament curled (UV Stabilized)	
Yarn type	7.200 / 8 dTex PE Monofilament curled	
Yarn thickness	140 um	
Yarn quality	Environmental friendly, free of lead and cadmium	
Primary backing	100% PP with fibre locked fleece, black, UV Stabilized, Weight 135 gr/m ²	
Secondary backing	Black Latex compound with a base of styrenebutadiene (SBR), Weight 836 gr/m ²	
Waterpermeability	60 liter/min/m ²	
Pile height	10 mm	
Face weight	1.040 gr/m ²	± 10%
Total weight	2.011 gr/m ²	± 10%
Tuft gauge	3/8 gauge	
Stitches per 10 cm linear	26	± 1%
Stitches per m²	27.300	± 10%
Colour	#47 Bicolor Green	
UV stability	Meets DIN 53387 Standard (6000 hours)	
Colour fastness	Xenon Test: Blue Scale > 7, Grey-scale > 4	
Colour lining	Not Applicable	
Roll width	400 cm	
Roll length	20-25m	
Applications	Multisport, Play area's	
Infill advice	Silica sand, gradation 0,5 - 1,0 mm, 80% roundshaped, appr 14 kg/m ²	
Comments	Before installation make sure the rolls are from the same production code (first five digits of the roll number) Project.	



Condor Grass has the right to alter each product specification in order to improve the carpet according to the newest technological applications. Condor Grass is not legally liable in case of non-compliance with the above mentioned specifications. The above mentioned specifications are for reference, and can only be used informal. The appearance of the final artificial grass carpet may change when it reaches temperatures beyond 75°C.